LABC Registered
Partner Authority Scheme

WarmerRoof

Quote & Order

Procedure

To request a quote for a Warmer Roof, fill out the quote request form and email to sales@warmerroof.com Please ensure all details are filled out correctly. We endeavour to return all quotes within 24 hours.

01373 473 900

sales@warmerroof.com

Order Process

1. When we have received your quote request form, our sales team will provide you with quotation outlining all details.

2. Once you are happy that everything on the confirmation is exactly as required, sign all pages and return to **orders@warmerroof.com** If you require any changes to be made prior to signing, send your updated quotation form to **sales@warmerroof.com** outlining all changes made.

3. The signed confirmation constitutes final approval for production. Please note any alterations made after you have returned the signed confirmation may be subject to charges.

4. Once signed confirmation is received, our team will send you a pro forma invoice via email. At that stage you will be required to pay 50% deposit (unless otherwise stated) This can be paid via bank transfer (bank details provided on invoice) If you would like to pay over the telephone please call Lorna OR Michelle on **01373473900 (option 1)**

5. Once your deposit is paid we will then commence to manufacture your Warmer Roof and will deliver your roof directly to your chosen destination, on our own transport. Please note delivery dates are subject to our delivery schedule and whist every effort will be made to accommodate your delivery date this may be subject to alteration, but any alteration to delivery dates will be notified.

Please ensure that **assistance** is available to **unload** your delivery at the delivery address, and that if a site delivery is required this is clearly indicated on your order. All deliveries will be made to your premises unless stated otherwise

In normal circumstances Local Authority Building Control is required for new or replacement conservatory roofs and it is the installers responsibility to check whether Building Control is required. Although the Warmer Roof has LABC accreditation, this does not mean that Building Control is not required but having this accreditation, through LABC, simplifies the Building Control application. It is likely that site inspection (s) will be carried out during the installation procedure of a replacement or new conservatory roof. Warmer Roof holds no responsibility if this advice is not followed. Warmer Roof will not take responsibility for any Building Control other than through our system approval scheme. Please contact a member of staff if any further guidance is required.

If in any doubt at any stage, please call our team who will be happy to assist. 01373 473 900

TILE OPTIONS

PLEASE NOTE TILES WILL COME DIRECT FROM OUR SUPPLIER ON A SEPARATE DELIVERY. ASSISTANCE REQUIRED.

WarmerRoof

Britmet Liteslate (min 12 degree pitch)

Sunset

Sunshine

Slate

Oak

Amethyst

Ash

Charcoal

Tapco Slate (min 12 degree pitch)

Stone Black

Pewter Grey

Brick Red

Plum

Chestnut Brown

Red Rock

Olive Green

Britmet Shingle (min 15 degree pitch)

Bramble Brown

Rustic Red

Moss Green

Smoked Oak

Raven

Titanium Grey

Rustic Brown

Rustic Terracotta

Tartan Green

Metrotile Shingle (min 15 degree pitch)

Charcoal

Antique Red

Forest Green

Burnt Umber

Coal Black

Bister Brown

Iron bark

Scarlet

Britmet Pantile 2000 (min 5 degree pitch)

Antique Red

Charcoal


Mid Grey

Sage Green

Terracotta

Tudor Brown

Pantile 2000 are full height sheet panels (not individule tiles) This product is made to measure and is only compatible with standard Lean-To roofs not involding hips.

COLOUR
OPTIONS

Ogee Guttering

White

Brown

Anthracite Grey

Black

Fascia & Soffit Board

White

Black Ash

Light Oak

Irish Oak

Rosewood

Anthracite

Cream

Chartwell Green

01373 473 900
sales@warmerroof.com

WARMER ROOF SURVEY SHEET

Date:

Company Name:

Job Reference:

Tel No:

WarmerRoof

01373 473 900 sales@warmerroof.com

The Workshop, Manor Road, Marston Trading Estate, Frome, Somerset, BA11 4BN

INTERNAL EAVES WIDTH (mm) **INTERNAL EAVES PROJECTION (mm**

PITCHED ROOF PLAN

ALWAYS MEASURE FROM YOUR INTERNAL FRAME

Please illustrate an accurate roof survey below with all host wall positions clearly marked . Please indicate all facet angles. All dimensions are internal frame and are in millimetres unless stated otherwise.

FRAMEWORK

Installer to ensure there is adequate support for this roof. Warmer Roof will not be held responsible for the failure of members, or existing structures supporting this roof.

Other (Please specify)

☐ 70mm

☐ **0.15 U-Value** ☐ **0.12 U-Value**

TILE COLOUR

- ☐ Tapco Slate — Lowest pitch = 12°
- ☐ Britmet Liteslate — Lowest pitch = 12°
- ☐ Britmet Shingle — Lowest pitch = 15°
- ☐ Metrotile Shingle — Lowest pitch = 15°
- ☐ Pantile 2000 — Lowest pitch = 5° *Only compatible with standard Lean- To roofs*

Tile colour:

Select from attached colour chart

.....

FASCIA

- ☐ White
- ☐ Cream
- ☐ Golden Oak
- ☐ Irish Oak
- ☐ Rosewood
- ☐ Anthracite Grey
- ☐ Black Ash
- ☐ Chartwell Green

VENTS

Please indicate position on survey above. Lowest pitch = 15°

- ☐ Small (550 x 780)
- ☐ Large (780 x 980)

Other: _____

Other sizes may result in a longer lead time

- ☐ Quantity Required
- ☐ Manual (pole supplied)
- ☐ Electric (make selection)
  - ☐ Remote & Rain Sensor
  - ☐ Solar

Extras

- ☐ Integral Blinds
- ☐ Pull down Blinds

EXTRAS

Please ensure these are priced separately quotation.

- ☐ External soffit (Depth 150mm)
- ☐ Internal pelmet (Depth 300mm)

SUPPORT

Steel reinforcement plate added to ring beam to support unsupported openings. Seek advice from a member of staff for maximum spans.

- ☐ Yes (Please indicate position on survey)
- ☐ No

GUTTER

(Ogee)

- ☐ White
- ☐ Brown
- ☐ Anthracite Grey
- ☐ Black

Downpipe

- ☐ Square
- ☐ Round

FIXED GLASS PLATES

Please indicate position on survey above. Lowest pitch = 12°

*** All glass plates run FULL HEIGHT of roof ***

- ☐ Yes ☐ No
- ☐ 600mm ☐ 800mm

Glass thickness - 28mm

ROOF HEIGHT

Roof pitch (degrees)

wall height from DPC (including cill)

(mm)

External height not to exceed from DPC to top of roof outside including tiles.

(mm)

- ☐ No height restriction
- ☐ Max height as above

WarmerRoof

Our dedicated team
are here to help

Finance@warmerroof.com
For all finance related queries

Factory@warmerroof.com
For any production issues

Info@warmerroof.com
For any component issues and updates for Tiles and Vents

Orders@warmerroof.com
For all order logging and processing

Sales@warmerroof.com
For all quotations and sales queries

Technical@warmerroof.com
For all technical queries and fitting assistance

Transport@warmerroof.com
For all Roof delivery queries